

AT 509 Lightweight 2500 dm³ portable water storage tank







b) of the RoHS Directive 2011/65/EC Annex II. recasting Directive 2002/95/EC, for cadmium (Cd), lead (Pb), mercury (Hg), hexavalent chromium (CrVI), polybrominated biphenyls (PBB) and polybrominated diphenyl ethers (PBDE). Testing performed by SGS-C-STC Standard Technical Service Co., Ltd.

PROTEK

OFFICE - Skromna 6, 93-405 Lodz, POLAND / CORRESPONDENCE ADDRESS - PROTEKT, Staroru	dzka 9, 93-403 Lodz, POLAND
SALES DEPARTMENT Phone +48 42 29-29-500, export@protekt.com.pl, fax +48 42 680-20-93 WAREHOUSE - Gombrowicza 6, 93-405 Lodz, POLAND	WWW.PROTEKT.UK

Dimensions when folded (bag):

Unfolding/folding time:

Tank fabric weight:

Tank fabric thickness:

120 x 50 x 36 cm

3 min

630 g/m²

0,5 mm

Lightweight 2500 dm^3 portable water storage tank AT 509



The kit includes:

- 1. Folding frame made of galvanised steel
- 2. tank made of PVC-coated fabric,
- 3. tank tarpaulin made of PVC-coated fabric,
- 4. carrying bag made of robust material.

The portable water storage tank with a capacity of 2500 dm³ is used to store water. It can be used in water supply systems during rescue and firefighting operations. The tank is equipped with a drain sleeve for removing water.

